



## SpecterDR 1.5x-6x

Based upon the battle-proven SpecterDR design, the SpecterDR 1.5x/6x provides higher magnification to enable greater precision and longer engagement ranges, while at the same time providing exceptional field of view in CQB mode.



The ELCAN SpecterDR 1.5x/6x is the second evolution in the family of Dual Role Optical Sights. The SpecterDR 1.5x/6x enjoys ELCAN's famous crystal-clear optics as well as a generous eye relief, making it the ideal instrument for designated marksman rifles and other long range applications. As with all SpecterDR sights, the magnification and field of view can be changed instantly with the throw of a lever. Depending upon the situation, the user may

adjust the sight to illuminate the crosshair or just a brilliant red dot in the center. Because the reticles are etched in glass, they are plainly visible even in the case of loss of electrical power due to battery failure or EMP.

The SpecterDR family offers the best single solution for Long Range and CQB engagements and is designed to withstand the rigors of modern professional use.



# SpecterDR 1.5x-6x



## FEATURE SPECIFICATION

<b>Magnification</b>	6x / 1.5x
<b>Length</b>	183mm nominal
<b>Width</b>	75mm nominal
<b>Height</b>	73mm nominal
<b>Weight</b>	705g nominal
<b>Reticle</b>	Dual-thickness ballistic crosshair with user-selectable red dot and VSOR rangefinder
<b>Aiming Dot diameter</b>	1.5 MoA @ 6x, 6 MoA @ 1.5x

## BALLISTIC CORRECTION

<b>DFOV156-C1:</b>	CX5455 reticle: 100-1000m for 5.56 NATO
<b>DFOV156-C2:</b>	CX5456 reticle: 100-1000m for 7.62 NATO
<b>CQB offset</b>	< 44mm @ 60m
<b>Field of View</b>	16 deg @ 1.5x, 4 deg @ 6x
<b>FoV @ 6x</b>	7 m @ 100 m (21 ft @ 100 yds)
<b>FoV @ 1.5x</b>	28.7 m @ 100 m (86 ft @ 100 yds)

<b>Illumination source</b>	Battery-powered LED
<b>Crosshair illumination</b>	5 settings, AN/PVS-22 night vision compatible
<b>Red Dot illumination</b>	5 settings, AN/PVS-22 night vision compatible
<b>Eye Relief</b>	70 mm
<b>Entrance pupil</b>	42mm
<b>Exit pupil</b>	7mm
<b>Nominal focus</b>	300m @ 6x, 105m @ 1.5x
<b>Fixed focus range</b>	20m to infinity
<b>Battery type</b>	CR2032 (3v Lithium)
<b>Battery life</b>	600 hours minimum, 3000 hours average
<b>Exterior finish</b>	Hard-anodized aluminum, gray/black color
<b>Adjustment resolution</b>	0.5 minute of angle
<b>Adjustment range</b>	120 minutes of angle
<b>Base requirement</b>	Mil-Std-1913 Picatinny Rail (Weaver compatible)
<b>Attachment</b>	ARMS Levers
<b>Shockproof</b>	450 g's
<b>Available accessories</b>	ARD (Anti-Reflection Device) Flip Covers