



1460TOOL

Protector

Mobile Tool Chest

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Also available without tray dividers
- Personalized nameplate service available
- **Adjustable and removable tray dividers for easy customization**
- **Top lid opens up to 180° for on-the-field anti-roll stability when open**
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handles
- Easy open Double Throw latches
- Lifetime Guarantee of Excellence (Tray system not covered by lifetime warranty)
- O-ring seal for dust and water resistant seal (IP66)
- Open cell core with solid wall design - strong, light weight
- Tray sizes: Top tray 17.65" x 8.2" x 2.4" (44.83 x 20.83 x 6.10 cm) and bottom tray 17.3" x 8.0" x 2.3" (43.94 x 20.32 x 5.84 cm)



DIMENSIONS

Interior (L x W x D)	18.54 x 9.92" x 10.92 (47.1 x 25.2 x 27.7 cm)
Exterior (L x W x D)	20.85 x 12.73" x 12.75 (53 x 32.3 x 32.4 cm)
Lid Depth	4.91" (12.5 cm)
Bottom Depth	6.01" (15.3 cm)
Total Depth	10.92" (27.7 cm)
Int Volume	1.16 ft ³ (0.033 m ³)

MATERIALS

Body	Polypropylene
Latch	EXL
O-Ring	Polymer
Pins	Stainless Steel
Foam	Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLORS

 Black	 Yellow	 Red
---	--	---

WEIGHT

Weight With Foam	13.00 lbs (5.9 kg)
Buoyancy	82.00 lbs (37.2 kg)

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com

TEMPERATURE

Document created on 05-20-19

Minimum Temperature -40°F (-40 °C)

Maximum Temperature 210°F (98.9 °C)

CERTIFICATIONS

IP66

OTHER

Nameplate yes

Military yes

ACCESSORIES
