

1470

Protector

Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- · Double safety locking latches with keys
- Automatic Pressure Equalization Valve balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck[™] with convoluted lid foam
- · Stainless steel hardware



CONFIGURATIONS



1470 Standard



1470NF No Foam



1470WF With Foam

DIMENSIONS

Interior (L x W x D) 15.70 x 10.70" x 3.87 (39.9 x 27.2 x 9.8 cm)

Exterior (L x W x D) 16.88 x 13.23" x 4.47 (42.9 x 33.6 x 11.4 cm)

 Lid Depth
 1.47" (3.7 cm)

 Bottom Depth
 2.40" (6.1 cm)

 Total Depth
 3.87" (9.8 cm)

 Int Volume
 0.38 ft³ (0.011 m³)

MATERIALS

Body ABS
Latch ABS
O-Ring Polymer
Pins Stainless Steel
Foam 1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com

COLORS

Document created on 05-29-19

Black

Desert Tan

WEIGHT

 Weight With Foam
 5.51 lbs (2.5 kg)

 Weight Empty
 4.28 lbs (1.9 kg)

 Buoyancy
 24.91 lbs (11.3 kg)

 Master Pack Weight
 22.20 lbs (10.1 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

CERTIFICATIONS

MIL C-4150J

FOAM PROPERTIES

Layer 1 (Lid) Layer 2 (Base) 1.50" Convolute 0.50" Pad

Layer 3 (Base) 1.83" Pick N Pluck

OTHER

Master Pack4NameplateyesMilitaryyes

ACCESSORIES