



1490

Protector

Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **Double safety locking latches with keys**
- **Fits notebook computers up to 17.3" L x 11.0" W x 3.3" D (43.94 x 27.94 x 8.38 cm)**
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware



CONFIGURATIONS



1490
Standard



1490NF
No Foam



1490WF
With Foam

DIMENSIONS

| | |
|-----------------------------|---|
| Interior (L x W x D) | 17.75 x 11.37" x 4.12 (45.1 x 28.9 x 10.5 cm) |
| Exterior (L x W x D) | 19.87 x 13.93" x 4.68 (50.5 x 35.4 x 11.9 cm) |
| Lid Depth | 1.50" (3.8 cm) |
| Bottom Depth | 2.62" (6.7 cm) |
| Total Depth | 4.12" (10.5 cm) |
| Int Volume | 0.48 ft³ (0.014 m³) |

MATERIALS

| | |
|---------------|---------------------|
| Body | ABS |
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

Purge Body

ABS

sales@pelican.com • www.pelican.com

Purge Vent

3 Micron Hydrophobic Non-Woven

Document created on 06-06-19

COLORS

■ Black

■ Desert Tan

WEIGHT

| | |
|---------------------------|---------------------|
| Weight With Foam | 6.50 lbs (2.9 kg) |
| Weight Empty | 5.47 lbs (2.5 kg) |
| Buoyancy | 41.00 lbs (18.6 kg) |
| Master Pack Weight | 27.30 lbs (12.4 kg) |

TEMPERATURE

| | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 210°F (98.9 °C) |

CERTIFICATIONS

Def Stan 81-41
STANAG 4280

FOAM PROPERTIES

| | |
|-----------------------|--------------------|
| Layer 1 (Lid) | 1.63" Convolute |
| Layer 2 (Base) | 0.38" Pad |
| Layer 3 (Base) | 2.25" Pick N Pluck |

OTHER

| | |
|--------------------|-----|
| Master Pack | 4 |
| Nameplate | yes |
| Military | yes |

ACCESSORIES