



1560LOC

Protector

Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **Padded removable sleeve for 15"-17" laptop computers**
- **Strong polyurethane wheels with stainless steel bearings**
- **Three removable accessory pouches**
- **Watertight, crushproof, and dustproof**
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Clothing compartment accommodates up to 5 days of travel apparel
- Comfortable rubber over-molded top and side handles
- Easy open Double Throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension handle
- This case may qualify as carry-on luggage on some airlines, check with your airline for more details



DIMENSIONS

Interior (L x W x D)	19.92 x 14.98" x 9.00 (50.6 x 38 x 22.9 cm)
Exterior (L x W x D)	22.07 x 17.92" x 10.42 (56.1 x 45.5 x 26.5 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	7.00" (17.8 cm)
Total Depth	9" (22.9 cm)
Int Volume	1.55 ft ³ (0.044 m ³)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLORS

 Black	 OD Green	 Desert Tan
---	--	--

WEIGHT

Weight With Foam	18.18 lbs (8.2 kg)
Weight Empty	17.00 lbs (7.7 kg)
Buoyancy	115.00 lbs (52.2 kg)

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

Master Pack Weight 21.00 lbs (9.5 kg) sales@pelican.com • www.pelican.com

TEMPERATURE

Document created on 05-21-19

Minimum Temperature -40°F (-40 °C)

Maximum Temperature 210°F (98.9 °C)

CERTIFICATIONS

IP67

Def Stan 81-41

STANAG 4280

OTHER

Wheels	2
Extendable Handle	yes
Master Pack	1
Nameplate	yes
Military	yes

ACCESSORIES
