

REFLEX MINI SIGHT SUB COMPACT

Minimize Your Carry, Maximize Your Accuracy
Tiny Optic, Big Performance



WWW.SHIELDSIGHTS.COM



PROUDLY DESIGNED, MANUFACTURED AND
ASSEMBLED IN GREAT BRITAIN

RMSsc - TECHNICAL SPECIFICATION

Optical Characteristics

Light Source	Red light emitting diode (LED) No laser; completely eye safe. No radioactive materials.
Red Dot Size Options	4MOA, 8MOA
Lens	Reflex x1 (no magnification) Parallax-free, crystal clear glass lens.
Lens Coating	Anti reflective colour free coating minimizes visible signature.
Lens Shape	Lens shape square (W x H) 17.35mm x 14.35mm / 0.68" x 0.56"

Electronics

Battery	CR1632 3V lithium metal battery.
Battery Fitting	Underside location.
Battery Life	9000 hours in average daylight with a CR1632.
Brightness Range	Lowest – compatible with night vision. Highest – visible against the sky in bright daylight.

Exterior

Housing material	Anodized aerospace grade aluminium (6082 T6).
Colour	Matte black.
Dimensions	Sight (L x W x H) 40.8mm x 19mm x 21.5mm / 1.60" x 0.74" x 0.84").
Weight	16.1 grams / 0.56 ounces without battery.
Mount	The SHIELD Footprint - 100+ Mounting solutions.
Water immersion	IP67

RMSsc

RMSsc - Open Mini Sight Sub Compact

The RMSsc follows the SHIELD ethos of fit, form and function offering EDC and CCW users new levels of comfort and concealability whilst retaining all the core SHIELD product features.

Designed from the ground up with size and concealability in mind, the new body promotes minimal drag and print signature. Ease of use allows the user maximum situational response time and removal of controls decrease potential failure points.

All whilst retaining our standard SHIELD footprint in one of the best looking products on the market.



WWW.SHIELDSIGHTS.COM