



# iSeries 3026-15 Case

3i-3026-15BE



SKB iSeries Injection Molded Mil-Standard Waterproof Cases are molded of ultra high-strength polypropylene copolymer resin, featuring a gasket-sealed, water and dust tight, submersible design (MIL-STD 810H) that is resistant to corrosion and impact damage.

Standard features include a molded-in hinge, padlock loops, Trigger Latch® System, snap-down rubber over-molded cushion grip handle, automatic ambient pressure equalization valve (MIL-STD 810H), and resistance to UV, solvents, corrosion, fungus and impact damage (MIL-STD

## FEATURES

---

- Think Tank-designed Nylex-wrapped fitted foam liner and (12) repositionable Nylex-covered foam pads with heavy duty hook-and-loop
- Built-in wheels and pull
- Reinforced locking loops for customer supplied
- Snap-down rubber over-molded cushion grip
- Waterproof and dust tight design (MIL-C-4150J /
- Molded-in hinge for added
- Trigger Latch®
- Ambient pressure equalization valve
- Resistant to UV, solvents, corrosion, fungus, and impact damage (MIL-STD

## SPECIFICATIONS

---

|          |      |   |
|----------|------|---|
| Exterior | Hard | - |
|----------|------|---|

|                            |          |          |
|----------------------------|----------|----------|
| Built In Wheels or Casters | Yes      | -        |
| Interior Length            | 30.75 in | 78.11 cm |
| Interior Width             | 26 in    | 66.04 cm |
| Interior Lid Depth         | 2 in     | 5.08 cm  |
| Interior Base Depth        | 13.5 in  | 34.29 cm |
| Interior Depth             | 15.5 in  | 39.37 cm |
| Product Weight             | 31.46 lb | 14.27 kg |
| Exterior Length            | 33.75 in | 85.72 cm |
| Exterior Width             | 28.5 in  | 72.39 cm |
| Exterior Height            | 16.25 in | 41.27 cm |
| Carton Length              | 34.5 in  | 87.63 cm |
| Carton Width               | 29 in    | 73.66 cm |
| Carton Height              | 17 in    | 43.18 cm |
| Shipping Weight            | 35.67 lb | 16.18 kg |
| Max Temp                   | 180 F    | 82.22 C  |
| Min Temp                   | -69 F    | -56.11 C |

## AVAILABLE CONFIGURATIONS

|              |       |              |
|--------------|-------|--------------|
| 3i-3026-15BE | Black | Empty        |
| 3i-3026-15BC | Black | Cubed Foam   |
| 3i-3026-15LT | Black | Padded Liner |