

EXFIL® BALLISTIC

PERFORMANCE STANDARDS

NIJ III-A | 9mm BFD < 25.4 mm DEF(AUST)10469 | 17gr V50 > 2400 ft/s Details on Back







SIZING	SIZE 1	SIZE 2

 Head Circumference (cm)
 52–60
 58–63

 Head Circumference (in)
 20.5–23.5
 23–24.75

 Hat Size (USA)
 6 5/8–7 1/2
 7 3/8–7 7/8

 ACH/MICH Size Equivalent
 S/M/L
 L/XL

Two sets of comfort pads (thin and thick) included with both sizes for further customization

COLORS

Black (FED-STD-595C #37031)

Coyote Brown (FED-STD-595C #20150)

MultiCam® (Hydrographic)

Ranger Green (Pantone 7770c)

Additional colors and hyrdographics available upon request

WEIGHT

Size 1 | Shell: 1.75 lbs (0.79 kg) | Complete System: 2.6 lbs (1.18 kg) Size 2 | Shell: 1.85 lbs (0.84 kg) | Complete System: 2.75 lbs (1.25 kg)

Complete system weight includes Helmet Shell, Accessory Rails, Impact Liner and Retention System



ENVIRONMENTAL CONDITIONS / MIL-STD-810G METHODS

501.5P1 High Temperature I 502.5P1 Low Temperature 507.5 Humidity I 509.5 Salt Fog I 510.5PII Blowing Sand/Dust 514.6 Loose Cargo Vibration I 500.5PI Low Pressure (Altitude)

SHELL ASSEMBLY

- Ballistic Performance: NIJ Level III-A (according to NIJ STD 0106.01/0108.01)
- > Fragment Performance: 17gr V50 ≥ 2400 ft/s (731 m/s)
- Backface Deformation: 9mm FMJ RN @ 1400 ft/s (425 m/s), BFD < 25.4 mm all locations
- Ballistic Certification: Certified by a third-party NIJ accredited laboratory
- High-cut shell with unique geometry for an optimal fit
- > Wilcox® W shroud for NVG mounts, compatible with retractable lanyard system
- > EXFIL® Rail 2.0 System or EXFIL® Rail 3.0 System available for side accessory rails

Materials

- > Shell: Polyethylene and other fibers in a proprietary composite matrix
- VELCRO® USA: Loop 1100, military loop
- > Hardware: Stainless steel with MIL-DTL-13924D black oxide coating
- Side Accessory Rails: Glass-reinforced polycarbonate

LINER SYSTEM

- > Three-piece Zorbium® foam impact liner with 16 individual comfort pads in two thicknesses, all Berry compliant materials
- Exceeds ACH Blunt Impact requirement per AR/PD10-02, 16Dec'13 average below 70G across all impacts and temperatures

Materials

- > Zorbium®: Proprietary polyurethane impact and comfort foam also used in the standard issue U.S. Army and Marine Corps 7-Pad System
- Impact Liner: Proprietary water-resistant film and loop fabric covering
- > Comfort Pads: Proprietary water-resistant film and antimicrobial wicking fabric covering

Size 1 Black Rail 2.0: 73-21S-E21 Size 2 Black Rail 2 0-73-225-F22 Size 1 Covote Brown Rail 2.0: 73-31S-E31

Size 1 MultiCam® Rail 2.0: 73-41S-E31 Size 2 MultiCam[®] Rail 2.0: 73-42S-E32

Size 2 Coyote Brown Rail 2.0: 73-32S-E32 Size 2 Ranger Green Rail 2.0: 73-72S-E72

Size 1 Black Rail 3.0: 73-R3-21S-E21 Size 2 Black Rail 3 0: 73-R3-22S-E22 Size 1 Ranger Green Rail 2.0: 73-71S-E71 Size 1 Covote Brown Rail 3.0: 73-R3-31S-E31 Size 2 Coyote Brown Rail 3.0: 73-R3-32S-E32 Size 1 MultICam® Rail 3.0: 73-R3-41S-E31 Size 2 MultlCam® Rail 3.0: 73-R3-42S-E32

Size 1 Ranger Green Rail 3.0: 73-R3-71S-E71 Size 2 Ranger Green Rail 3.0: 73-R3-72S-E72

RETENTION

- > Team Wendy® CAM FIT™ Retention with Boa® Fit System for optimized stability and fit
- > Features boltless design with high-strength hook/loop attachment, meets ACH pull strength requirements
- > Cam Lock sliders for one-handed adjustment and secure fit
- > Left eye dominant option available

Materials

- > Boa® Fit System with micro-adjustable dial, coated stainless steel cable and low friction guides
- MIL-DTL-32067 leather chin cup

- > 5/8" nylon webbing
- Acetal buckles and cams
- > 500D Cordura nape pad with Zorbium® foam
- Antimicrobial wicking headband sleeves

AVAILABLE ACCESSORIES

SHOCK CORD KIT INCLUDED

EXFIL® BALLISTIC HELMET COVERS

Mesh and Nylon spandex cover available in Black, Coyote Brown, MultiCam®, MultiCam® Alpine, Ranger Green and Wolf Gray

EXELL® BALLISTIC FAR COVERS

Extend NIJ III-A ballistic coverage to greater than full-cut ACH

EXELL® OXYGEN MASK STRAP KIT

For attachment of Airborne Systems SOLR® and PHAOS, and Cobham PHANTOM O2 masks

EXFIL® PELTOR™ HEADSET ADAPTERS

Provides direct rail mount of all Peltor™ ComTac™ systems (quick release optional for EXFIL® Rail 2.0; required for EXFIL® Rail 3.0)

EXFIL® OUICK RELEASE RAIL ADAPTERS

Tool-free accessory attachment, includes two 5-slot Picatinny rails

EXFIL® RAIL 2.0 ACCESSORY KIT

Includes two goggle posts and two "MINI-TINNY" 2-slot Picatinny rails (MINI-TINNY not compatible with EXFIL® Rail 3.0)