



AR15 OPS READY COLLAPSIBLE STOCKS



MADE IN USA

USER MANUAL

MUP004011508

Company Introduction

Leapers started the UTG PRO line of Made in USA products in 2009. Since then, we have grown from one carbine quad rail handguard to offering a wide variety of items. Our manufacturing operation is equipped with dozens of CNCs, including some robot-automated high end machines usually used for making precision aerospace and medical equipment. We also acquired the most advanced RoboShot polymer injection machines to manufacture innovative high quality polymer products. In answering market demands, we dedicated part of our manufacturing space to implement an in-house Cerakote™ painting facility. The growing popularity and recognition of our UTG PRO products continues to fuel our commitment and endeavor to provide consumers with USA made products that can compete at every level. You can count on Leapers to persevere in this manufacturing journey and we welcome and value the continuous support from our loyal customers.

The Best Never Rest Warranty - Lifetime

Leapers, Inc. warrants that all UTG & UTG PRO products conform to published specifications and are free from defects in material and workmanship. We will repair or replace defective products for the duration of the product's life span. Our dedicated and professional in-house customer service team will go above and beyond to make things right and provide the best in-class customer service experience you expect to receive.

Our warranty does not extend to products damaged from misuse, accidental damage, negligence, natural disasters/accidents, or unauthorized repair or alteration.

For warranty service, please submit your inquiry by visiting our customer service page on our website at www.leapers.com or give us a call at 734-542-1500. A Return Authorization Number (RMA) must be assigned before returning any products for warranty service.

Disclaimer and Limitation of Liability


Leapers is pleased to offer suggestions of the use of its products, however Leapers neither assumes responsibility for any omissions or errors nor assumes liability for any damages that result from the use of its products in accordance with information provided by Leapers, whether verbal or written.

EXCEPT FOR THE EXPRESS WRITTEN WARRANTY SPECIFICALLY SET FORTH ABOVE, ALL EXPRESS AND IMPLIED REPRESENTATIONS AND WARRANTIES ARE HEREBY DISCLAIMED, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, NON-INTERFERENCE, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR WARRANTY OF ACCURACY OF ANY INFORMATION PROVIDED WHETHER WRITTEN OR ORAL. ALL WARRANTIES ARISING FROM ANY COURSE OF DEALING, LAW, USAGE OR TRADE PRACTICE ARE HEREBY EXPRESSLY EXCLUDED TO THE EXTENT ALLOWED BY LAW. TO THE EXTENT AN IMPLIED WARRANTY CANNOT BE EXCLUDED, SUCH WARRANTY IS LIMITED IN DURATION TO ONE YEAR. SOME STATES OR JURISDICTIONS DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU.

UNDER NO CIRCUMSTANCES IS LEAPERS, OR ITS SUPPLIERS OR RESELLERS LIABLE FOR ANY OF THE FOLLOWING EVEN IF INFORMED OF THEIR POSSIBILITY: 1) THIRD PARTY CLAIMS AGAINST YOU FOR DAMAGES; 2) SPECIAL, INCIDENTAL, OR INDIRECT DAMAGES OR FOR ANY ECONOMIC CONSEQUENTIAL DAMAGES; OR 3) LOST PROFITS, BUSINESS REVENUE, GOODWILL, OR ANTICIPATED SAVINGS. SOME STATES OR JURISDICTIONS DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU.

PART(S) INCLUDED

(STOCK ONLY FOR CERTAIN MODELS)



BATTERY COMPARTMENT

(FOR S1 STOCK SERIES ONLY)



Remove either of the rubber end caps by firmly pulling it away from the stock and pulling outward until it clears the battery channel. Once batteries are inserted into the chamber, plug the rubber end cap back in securely.

CHEEK REST REMOVAL AND INSTALLATION

(FOR MODELS WITH CHEEK REST ONLY)



To remove the Cheek Rest from the stock simply slide it off by pulling it forward towards the stock's opening for the Extension Tube.

To install the Cheek Rest onto the stock simply slide it on and push its rearward towards the stock's butt pad until you hear the "click" of the Cheek Rest's locking detent securely engaging with the stock.


QD SLING SWIVEL HOUSING INSTALLATION



The Reversible QD Sling Swivel Housing can be installed on either the right or left side of the stock to accommodate left or right handed shooters. Use a 1/8" Allen wrench and a 5/16" socket for installation.

COLLAPSIBLE STOCK ASSEMBLY

Caution: Make sure firearm is not loaded. Remove magazine and examine chamber. Use safe handling procedures at all times. For detailed instructions on disassembly or reassembly of your specific firearm, contact the manufacturer or consult your owner's manual.



Caution: Buffer Spring and Recoil Buffer are compressed inside the Extension Tube and held in place by a yellow colored cap. These parts are under spring pressure. To access these parts, point the cap downward in a safe direction and hold firmly while slowly unscrewing the cap from the Extension Tube until it is removed.



Remove the Stock from the Extension Tube by lifting up on the Adjustment Latch while simultaneously sliding the Stock off the tube. Remove the Castle Nut and Tear-Drop Ring from the tube.



Install the Castle Nut first onto the Extension Tube with the four wrench cutouts facing towards the rear of the Extension Tube away from the threads. Install the Tear-Drop Ring back onto the Extension Tube as shown.



With the Tear-Drop Ring and Castle Nut in place on the Extension Tube, Install the Extension Tube into your lower receiver by pressing the buffer detent down and threading the Extension Tube until the tube overlaps the shoulder of the buffer detent. Make sure the Extension Tube is positioned correctly with the 6 position holes pointing downward.



Press the Tear-Drop Ring into the receiver while making sure the take down pin detent spring goes straight back into the recess of the lower receiver.



With the Tear-Drop Ring held in place, hand tighten the Castle Nut by rotating clockwise until the Tear-Drop Ring is flush against the lower receiver.



Securely tighten the Castle Nut with an AR15 armorer's wrench. Do not over tighten.



Reinstall the stock onto the Extension Tube by lifting up on the Adjustment Latch while simultaneously sliding the stock on to the tube until it locks in place.



Install the Recoil Spring and Recoil Buffer into the Extension Tube until the Recoil Buffer clicks into place against the buffer detent.



Reassemble the rifle and test for proper function.