



CROSSFIRE® HD

RIFLESCOPES COMPARISON SHEET



CROSSFIRE® HD										
CONFIGURATION	1-4x24	1.5-5.5x32 Scout	2-7x32	2-7x32	3-9x40	3-9x40	4-12x44	4-12x44	6-18x50	6-18x50
SKU	CFR-1401i	CFR-1501i	CFR-2702 CFR-2702R	CFR-2701i	CFR-3901 CFR-3902 CFR-3901SW CFR-3901MZ	CFR-3901i	CFR-41201 CFR-41202	CFR-41201i	CFR-61802	CFR-61801i
RETICLE	Illuminated Dead-Hold® 2A BDC MOA	Illuminated Dead-Hold® 2A BDC MOA	V-Plex MOA	Illuminated Dead-Hold® 2A BDC MOA	Dead-Hold® BDC MOA V-Plex MOA Straight-Wall BDC MOA Muzzleloader BDC MOA	Illuminated Dead-Hold® 2A BDC MOA	Dead-Hold® BDC MOA WideRange Plex™ MOA	Illuminated Dead-Hold® 2A BDC MOA	WideRange Plex™ MOA	Illuminated Dead-Hold® 2A BDC MOA
FOCAL PLANE	SFP	SFP	SFP	SFP	SFP	SFP	SFP	SFP	SFP	SFP
ILLUMINATION SETTINGS	6 Daylight	6 Daylight	N/A	6 Daylight	N/A	6 Daylight	N/A	6 Daylight	N/A	6 Daylight
EYE RELIEF	3.8"	1.5x: 9.0" - 24.0" 5.5x: 9.0" - 13.0"	3.9"	3.9"	3.8"	3.8"	3.8"	3.8"	3.8"	3.8"
LINEAR FIELD OF VIEW (@ 100 YDS.)	109.5' - 26.7'	23.0' - 6.8'	53.1' - 14.8'	53.1' - 14.8'	37.2' - 12.4'	37.2' - 12.4'	26.9' - 8.6'	26.9' - 8.6'	18.7' - 6.0'	18.7' - 6.0'
TURRET STYLE	Capped	Capped	Capped	Capped	Capped	Capped	Capped	Capped	Capped	Capped
TUBE SIZE	30mm	1"	1"	1"	1"	1"	1"	1"	30mm	30mm
ADJUSTMENT GRADUATION	1/2 MOA	1/4 MOA	1/4 MOA	1/4 MOA	1/4 MOA	1/4 MOA	1/4 MOA	1/4 MOA	1/4 MOA	1/4 MOA
TRAVEL PER ROTATION	30 MOA	15 MOA	15 MOA	15 MOA	15 MOA	15 MOA	15 MOA	15 MOA	15 MOA	15 MOA
MAX ELEVATION ADJUSTMENT	130 MOA	100 MOA	90 MOA	90 MOA	72 MOA	72 MOA	70 MOA	70 MOA	70 MOA	70 MOA
MAX WINDAGE ADJUSTMENT	130 MOA	100 MOA	90 MOA	90 MOA	72 MOA	72 MOA	70 MOA	70 MOA	70 MOA	70 MOA
PARALLAX SETTING	100 yds.	100 yds.	100 yds. / 50 yds.	100 yds.	100 yds.	100 yds.	15 yds. - ∞	15 yds. - ∞	10 yds. - ∞	10 yds. - ∞
LENGTH	9.5"	8.7"	11.2"	11.2"	12.5"	12.5"	13.4"	13.4"	13.9"	13.9"
WEIGHT	15.3 oz.	11.6 oz.	14.7 oz.	15.7 oz.	16.2 oz.	17.1 oz.	20.7 oz.	21.5 oz.	22.6 oz.	23.2 oz.

VORTEXOPTICS.COM

© 2025 Vortex Optics ® Registered Trademark and TM Trademark of Vortex Optics

