

**MAINTENANCE:** Wiley X lenses are specially coated to offer superior abrasion resistance. Please follow below instructions to prolong the life of your lenses and keep them performing at their best:

Clean lenses with lukewarm water only.

Do not use solvents or special cleaners.

Use micro-fiber cleaning cloth provided to gently wipe clean.

Never use paper products to clean and avoid wiping lens surface when dry and/or dirty as this may potentially scratch the lens.

**WARNING:** Wiley X brand eyewear is tested tough. However, impact resistant eyewear is not unbreakable and does not provide unlimited eye protection under all circumstances and conditions. Misused, abused, scratched and/or damaged eyewear can reduce impact protection (and void your limited warranty). Dirty and/or wet eyewear can impair vision and reduce safety (resulting in personal injury and/or property damage). Keep your Wiley X eyewear clean with water only. Do not use solvents or abrasives as it could scratch or damage the product reducing its effectiveness. Store your Wiley X eyewear in the protective case provided to prolong the life of the lenses. Most of all, take all appropriate precautions when wearing your Wiley X eyewear during hazardous and/or dangerous activities and conditions. Wiley X, Inc. is not responsible for personal injury, property damage or losses incurred while using Wiley X brand products.



**WILEY X INC: 1.800.776.7842 // 925.243.9810 // WILEYX.COM**

7800 PATTERSON PASS ROAD, LIVERMORE CA 94550 USA

**WILEY X EUROPE LLC: +45 96 93 00 45 // WILEYX.EU**

SØNDERGADE 8-10 7570 VEMB DENMARK

ERX-R8052T [0]



# NERVE R-8052T INSTRUCTIONS

**COPYRIGHT © 2015 WILEY X, INC. ALL RIGHTS RESERVED.**

WILEY X, WX, BLACK OPS, logos, tag lines and product names are trademarks or registered trademarks (marcas registradas) of Wiley X, Inc. in the U.S. and other countries. Logos © 2007-2015 Wiley X, Inc. All rights reserved.


## LENS REMOVAL

Position hands as shown in drawing. Separate the top of the goggle from lens. Disengage both outside corners of the lens from the frame. Separate nose piece from the frame.




## LENS INSTALLATION

Install lenses in reverse of lens removal, starting with engaging nose piece area. Snap together making sure all lens hooks are seated.



## GOGGLE STRAP / GOGGLE FRAME

Secure the goggle strap by inserting the strap pin at [1] into the goggle face frame at [2].



Remove or attach goggle strap by positioning the strap perpendicular to the frame as pictured above.

